

Technical features:

- electric steel towel warmer radiator
- horizontal elements with rectangular tubes 50x10 mm manifolds
- side manifolds with a 30 mm round section
- complete with thermal liquid and an auxiliary electrical power system that reaches 1000 Watt.

This auxiliary power system is combined with a fan to ensure the temperature set in the environment where it is used.

Price included:

- 4 adjustable wall fixing brackets in the same color as the radiator
- Wireless remote control

Finishes available	Surcharge
Standard White	
Classic finished	
Special finished	
Other RAL colors	

Finishing codes see page 596.




Booster



MAIN CHARACTERISTICS OF AIR DIFFUSER

- ON/OFF switch
- Power supply 230 V 50 Hz, 1 ph
- Power installed = 1000 W
- Insulation: CLASS II
- Protection index: IP24
- Long electricity cable: 1.200 mm, SCHUKO plug
- Wireless remote control



The Standard White radiator is combined with an air diffuser in the same colour; coloured radiators feature a chromium-plated air diffuser.
The radiator is not reversible.
The radiator will be supplied with the resistance always mounted on the right side.

Standard White colour code - for different colour codes see the colors page

Wireless Remote Control

- Wireless communication via radio signals transmitted to the receiver connected to the system
- Radiofrequency communication pursuant to European standards
- Operating modes: Manual, Automatic, Comfort, Economy, Holidays
- You can activate 3 manual functions, automatic and holiday
- Can be set comfort temperature of 5°C to 30°C
- Optional ITCS (Intelligent Temperature Control System)
- Open window detection function

